

Mobile Power

1800 RPM Diesel

Standby Power Ratings

60HZ	kVA 48	kW 38
------	--------	-------

Continuous Power Ratings

60HZ	kVA 44	kW 35
------	--------	-------



Made in USA
Generator available
with or without trailer

Baldor Mobile Power Generator Features

- Brushless generator for long life, low maintenance
- 3 position reconnection switch for easy voltage selection
- Voltage regulation 1/2%
- Baldor control system: All operator controls are located behind one lockable panel door
- Automatic safety shutdowns with indicator lights: low oil pressure, high water temp., engine overcrank, engine overspeed
- Industrial grade, self-priming Isuzu engine
- Illuminated instrumentation panel
- 50 or 60 hertz frequency
- Circuit breaker - main
- Circuit breakers - outlets
- Single point removable lifting eye
- 6 bolts to remove generator from trailer
- Cold start aid - glow plugs
- Fuel/water separator
- Generator available with trailer (TS45T) or without trailer (TS45S)
- Automatic start feature (with optional transfer switch)
- Lighted license plate bracket
- Premium grade DOT approved tandem axle highway trailer featuring: torsion bar suspension (no more broken leaf springs), diamond plate aluminum fenders, leveling jack, running lights, surge brakes
- Heavy gauge steel sound attenuated enclosure with muffler
- Durable powder coat paint finish
- Lockable door panels
- Long run internal fuel tanks
- Warranty:
 - limited 3 year warranty
 - 1 year or 3000 hours parts and labor
 - 3 year or 3000 hours parts

Options

- Electronic governor
- Electric brakes
- Block heater
- Battery charger
- Ball hitch (3" pintle hitch standard)
- Automatic transfer switches
- Generator without trailer

Generator Specifications

Standby Output 150° Rise kVA/kW:

Single phase voltage @ 240V	27/27
3 phase voltage @ 208V	46/37
3 phase voltage @ 240V	46/37
3 phase voltage @ 480V	48/38

Continuous Output 125° Rise kVA/kW:

Single phase voltage @ 240V	25/25
3 phase voltage @ 208V	44/35
3 phase voltage @ 240V	44/35
3 phase voltage @ 480V	44/35

Amperage (Continuous) kVA/kW:

Single phase amperage @ 240V/120V	104.2/208.3
3 phase amperage @ 208V	121.4
3 phase amperage @ 240V	105.3
3 phase amperage @ 480V	52.6

Voltage-3 phase adjustable . 208/220/240/416/440/460/480

Voltage-Single phase adjustable .120/127/139/240/254/277

3 phase power factor	0.8
Voltage regulation	1/2%
Frequency	50 or 60 Hertz
Total harmonic distortion	<5%
Insulation	Class F

Engine Specifications

Manufacturer	Isuzu
Model	4BG1
Cylinders	4
Induction system	Naturally aspirated
Displacement, L (cu. in.)	4.3L (264.2)
HP @ rated speed	64.0
RPM	1800
Bore and stroke	4.13" x 4.92"
Lubrication capacity (with filter)	13.7 Qts
Battery recommendation min. (cold cranking amps)	900
- Battery rack and cable supplied (battery not included)	
- Spin-on oil filter	
- Thermostat controlled cooling system	
- 12V engine alternator	
- 12V starter motor	

Ratings: - **Standby Ratings:** Standby ratings are applicable for supplying emergency power for the duration of a utility power outage. Primary power to the installation is utility supplied. No overload capability for standby rating. Standby ratings in accordance with ISO 3046, BS55114, DIN 6271. **Continuous Power Rating:** Continuous power is the maximum power available for continuous duty. A 10% overload capacity is available for 1 hour out of 12 hours of operation. For additional information, please consult factory. Manufacturer reserves the right to implement specifications or design changes without notice. **WARNING:** Do not connect generator to any building's electrical system unless a disconnect switch has been installed.

Distributed by:

BALDOR
GENERATORS

3815 Oregon Street • Oshkosh, WI 54902
1-800-872-7697 • (920) 236-4200 • Fax (920) 236-4219

World Headquarters

Baldor Electric Company • P.O. Box 2400 • Fort Smith, AR 72902-2400 U.S.A.
Phone (479) 646-4711 • Fax (479) 648-5792 • International Fax (479) 648-5895

www.baldor.com

Receptacle Specifications

120 Volt 20 Amp GFCI	6
120/240 Volt CS6369 Twistlock	3
Two wire remote start capability	Yes

Fuel System Specifications

Fuel consumption (GPH):

1/2 load	2.0
Full load	3.4
Fuel	Diesel

Approximate run time (Hours):

1/2 load	40
Full load	24
Fuel Capacity (Gal.)	80

Weights and Dimensions

Weight without fuel	3540
Weight without fuel and without trailer	2829
Dimensions with trailer (L x W x H)	147" x 60" x 81"
Dimensions without trailer (L x W x H)	84" x 38" x 61"

Sound Level

Sound level dB(A)	67
7 meters, full load	

Engine, Generator Instrumentation

Voltmeter, ammeter, frequency meter, phase selector switch, oil pressure gauge, water temperature gauge, battery voltmeter, start/stop/auto switch, voltage adjusting rheostat, elapsed time meter, individual fault shutdown lights, panel lights with switch, receptacle panel

